

according to Regulation (EC) No 1907/2006

**freeform® bond**

Revision date: 11.08.2016

Product code: 10571.2

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

freeform® bond

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Ligth curing repair material for use in dentistry

**1.3. Details of the supplier of the safety data sheet**

Company name:	DETAX GmbH & Co. KG	
Street:	Carl-Zeiss-Strasse	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.de	
Internet:	www.detax.de	
Responsible Department:	Emergency number:	

+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

**1.4. Emergency telephone****number:**

+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 - 4.00 p.m.)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1A

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"  
acrylic acid derivates

vinylester resin

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

**Signal word:** Danger

according to Regulation (EC) No 1907/2006

**freeform® bond**

Revision date: 11.08.2016

Product code: 10571.2

Page 2 of 9

**Pictograms:**

**Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/ container in accordance with legal and national regulations.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Mixture of acrylic/ methacrylic resins with auxilliary matters.

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"	20 - 70 %
	201-297-1	607-035-00-6
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
	acrylic acid derivates	25 - 50 %
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 3; H319 H317 H412	
	aliphatic polyestertriurethane triacrylate	5 - 20 %
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	
55818-57-0	vinylester resin	1 - < 5 %
		01-2119490020-53
	Skin Sens. 1; H317	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	0,1 - 5 %
	278-355-8	015-203-00-X
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361f H317 H411	

Full text of H and EUH statements: see section 16.

according to Regulation (EC) No 1907/2006

**freeform® bond**

Revision date: 11.08.2016

Product code: 10571.2

Page 3 of 9

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Provide fresh air. Medical treatment necessary.

**After contact with skin**

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours can form explosive mixtures with air.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

according to Regulation (EC) No 1907/2006

### freeform® bond

Revision date: 11.08.2016

Product code: 10571.2

Page 4 of 9

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### **Advice on storage compatibility**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

##### **Further information on storage conditions**

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep away from all kind of lighth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

#### 7.3. Specific end use(s)

Adhesive for repair of dental restorations like prosthesis, crowns or bridges  
For use by trained specialist staff.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### **Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### **Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

##### **Eye/face protection**

Suitable eye protection: goggles.

##### **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

##### **Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

according to Regulation (EC) No 1907/2006

### freeform® bond

Revision date: 11.08.2016

Product code: 10571.2

Page 5 of 9

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: light yellow  
 Odour: faintly like esters

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined  
 Initial boiling point and boiling range: 92 °C DIN 51356  
 Flash point: 12 °C DIN 51755

#### Flammability

Solid: not applicable  
 Gas: not applicable

Lower explosion limits: 2 vol. %  
 Upper explosion limits: 12 vol. %  
 Ignition temperature: >400 °C DIN 51794

#### Auto-ignition temperature

Solid: not applicable  
 Gas: not applicable

Decomposition temperature: >100 °C

#### Oxidizing properties

Not oxidizing.

Vapour pressure: 40 hPa  
 (at 20 °C)

Vapour pressure: 160 hPa  
 (at 50 °C)

Density (at 20 °C): 1,07 g/cm<sup>3</sup> DIN 51757

Water solubility: 16 g/L  
 (at 20 °C)

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

#### 9.2. Other information

Solid content: not determined

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable.

#### 10.2. Chemical stability

according to Regulation (EC) No 1907/2006

### freeform® bond

Revision date: 11.08.2016

Product code: 10571.2

Page 6 of 9

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Reacts with : oxidising agents, radicals forming substances or heavy metal ions.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

Ultra-violet lighth and daylighth initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of lighth. Keep in a refrigerator at 2°C - 12°C / 36°F - 54 °F.

#### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"				
	oral	LD50	7870 mg/kg	Rat	
	dermal	LD50	>5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	78 mg/l	Rat	
	acrylic acid derivates				
	oral	LD50	2000 mg/kg	Rat	OECD 423
	dermal	LD50	2000 mg/kg	Rabbit	OECD 402
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rat	

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"); (acrylic acid derivates); (vinylester resin); (diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA")

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

### freeform® bond

Revision date: 11.08.2016

Product code: 10571.2

Page 7 of 9

#### Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

### SECTION 12: Ecological information

#### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"				
	Acute fish toxicity	LC50	>100 mg/l	96 h	
	acrylic acid derivatives				
	Algae toxicity	NOEC	10 mg/l	72 d	Pseudokirchneriella subcapitata OECD 201
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	Acute algae toxicity	ErC50	>2,01 mg/l	72 h	Scenedesmus subspicatus
	Acute crustacea toxicity	EC50	3,53 mg/l	48 h	Daphnia magna (Big water flea)
	Acute bacteria toxicity		(>1000 mg/l)	3 h	Activated sludge

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
		0-10%	28	
	Not readily biodegradable (according to OECD criteria)			

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

#### BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47-55	Cyprinus carpio (Common Carp)	

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

#### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**freeform® bond**

Revision date: 11.08.2016

Product code: 10571.2

Page 8 of 9

**Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L/ 30kg
Hazard No:	33
Tunnel restriction code:	D/E

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Marine pollutant:	nein
Special Provisions:	-
Limited quantity:	5L/ 30kg
EmS:	F-E, S-E

**Other applicable information (marine transport)**

Flash point: 12°C c.c.

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Limited quantity Passenger:	1 L/ 30 kg
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### freeform® bond

Revision date: 11.08.2016

Product code: 10571.2

Page 9 of 9

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*