Renfert GmbH



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720\_AUS\_IV Page 1 of 6

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Isofix 2000 1720 2000

Further trade names

1720 2000 Isofix 2 x 1 I 1720 1000 Isofix spray bottle

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Isolation Spray plaster against plaster.

### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen

Telephone: +49 7731 8208-0 Telefax: +49 7731 8208-70

e-mail: info@renfert.com Internet: www.renfert.com

Supplier

Company name: Ivoclar Vivadent Pty. Ltd. Street: 1-5 Overseas Drive

Place: - Noble Park North VIC 3174

Telephone: + 61 3 9795 9599 Telefax: + 61 3 9795 9645

1.4. Emergency telephone number: 131 126 (Poisons Information Centre - 24 hours / 7 days)

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Flammable liquid and vapour. Causes serious eye irritation.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

Signal word: Warning Pictograms:





### **Hazard statements**

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

# **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## Chemical characterization

Isolation agent





according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720\_AUS\_IV Page 2 of 6

#### Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	GHS Classification	GHS Classification				
67-63-0	propan-2-ol					
	200-661-7	603-117-00-0	01-2119457558-25			
	Flam. Liq. 2, Eye Irrit. 2,					

Full text of H and EUH statements: see section 16.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General information

Immediately remove any contaminated clothing, shoes or stockings.

#### After inhalation

Provide fresh air.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

#### After contact with eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

# Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

#### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## Advice on safe handling

Use only in well-ventilated areas. Avoid contact with eyes and skin.





according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720\_AUS\_IV Page 3 of 6

When using do not eat, drink or smoke.

#### Advice on protection against fire and explosion

Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking.

Vapours are heavier than air.

Take precautionary measures against static discharges.

#### Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

#### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### Further information on storage conditions

Protect against: Heat

Recommended storage temperature: +10°C / 50°F - +30°C / 86°F

#### 7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

# Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### 8.2. Exposure controls

### Appropriate engineering controls

Safe handling: see section 7

#### Protective and hygiene measures

Do not breathe vapour.

Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

## Eye/face protection

Wear eye/face protection.

### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,4 mm

Breakthrough time: > 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

## Respiratory protection

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

Respiratory protection necessary at: insufficient ventilation

# Environmental exposure controls

Do not allow to enter into surface water or drains.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: light yellow
Odour: characteristic

Test method

pH-Value (at 20 °C): 9 DIN 19268

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: > 82 °C Literaturwert





according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720 AUS IV Page 4 of 6

Sublimation point: not applicable

Flash point: 30 °C DIN EN ISO 13736

Flammability

Solid: not applicable
Gas: not applicable

**Explosive properties** 

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 2,0 \* vol. % Upper explosion limits: 12,0 \* vol. %

Ignition temperature: > 425 \* °C Literaturwert

Decomposition temperature: not determined

**Oxidizing properties** 

not relevant

Vapour pressure: <41 hPa Literaturwert

(at 20 °C)
Vapour pressure: < 225 hPa Literaturwert

(at 50 °C)

Density (at 20 °C): 0,92 - 0,98 g/cm³
Bulk density: not applicable
Water solubility: very soluble

Solubility in other solvents

miscible with most organic solvents

Partition coefficient: not applicable Viscosity / dynamic: not determined

Flow time: < 30 s (3mm) 3 DIN EN ISO 2431

(at 23 °C)

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

\* Data apply to the technically active substance

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

# 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Violent reaction with: Oxidising agent, strong

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

# Acute toxicity

Based on available data, the classification criteria are not met.

### Irritation and corrosivity

Causes serious eve irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.





according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720\_AUS\_IV Page 5 of 6

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### **Further information**

The product has not been tested. The statement is derived from the properties of the single components.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol					
	Acute bacteria toxicity	(> 100 mg/l)				

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No information available.

### **Further information**

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## Disposal recommendations

Dispose of waste according to applicable legislation.

# Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number:** UN 1987

14.2. UN proper shipping name: ALKOHOLE, N.A.G. (2-Propanol Mischung)

14.3. Transport hazard class(es): 3
14.4. Packing group: III

# Marine transport (IMDG)

**14.1. UN number:** UN 1987

14.2. UN proper shipping name: ALCOHOLS, N.O.S. (2-propanol mixture)

14.3. Transport hazard class(es):314.4. Packing group:IIIMarine pollutant:no

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1987

**14.2. UN proper shipping name:** Alcohols, n.o.s. (2-propanol mixture)





according to Regulation (EC) No 1907/2006

Isofix 2000 1720 2000

Revision date: 11.11.2020 Product code: 1720\_AUS\_IV Page 6 of 6

14.3. Transport hazard class(es):314.4. Packing group:III

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Further information: see section 6, 7, 8

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 189 g/l

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Regulation (EC) No 1005/2009 (Ozone depleting substances): not applicable Regulation (EU) 2019/1021 (persistent organic pollutants): not applicable

Regulation (EU) No 649/2012 (export and import of hazardous chemicals): not applicable

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Eye Irrit. 2; H319	Calculation method

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)