according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Periomat Intra Fixer concentrate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Special X-ray set for Dürr developers.

Product Categories [PC]

PC30 - Photo-chemicals

Uses advised against

None, if handled according to order.

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

orochemie GmbH + Co. KG

Street: Max-Planck-Straße 27

Postal code/city: 70806 Kornwestheim

Telephone: +49 7154 1308-0 **Telefax:** +49 7154 1308-40

Information contact: DÜRR DENTAL SE, Höpfigheimer Str. 17, 74321 Bietigheim-Bissingen, Germany

Tel: +49 7142 705-0, Fax: +49 7142 705-500, info@duerrdental.com

in Great Britain/Ireland:

DÜRR DENTAL [Products] UK Ltd., 14 Linnell Way - Telford Way Industrial Estate, Kettering Northants NN16 8PS,

United Kingdom

Tel: +44 1536 526740, Fax.: +44 1536 526749, info@duerruk.com

1.4 Emergency telephone number

INT: +49 6132 84463 (24 h/7 d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Although there is no labelling required for this product, we nevertheless advise observation of the safety recommendations.

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Classification procedure

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements

P280 Wear protective gloves and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P353 Rinse skin with water/shower.

P501 Dispose of contents/container to hazardous or special waste collection point.

Special rules for supplemental label elements for certain mixtures

EUH210 Safety data sheet available on request.

Page: 1/9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Periomat Intra Fixer concentrate contains ammonium thiosulfate, sodium sulfite, organic acids, complexing and auxiliary agents in aqueous solution.

Hazardous ingredients

ACETIC ACID; REACH registration No.: 01-2119475328-30; EC No.: 200-580-7; CAS No.: 64-19-7

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash with plenty of water. When in doubt or if symptoms are observed, get medical advice.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder Water spray Water mist The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

None known.

Hazardous combustion products

None known.

5.3 Advice for firefighters

Page: 2/9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

Adapt protective equipment to surrounding fire.

Special protective equipment for firefighters

Adapt protective equipment to surrounding fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Personal protection equipment

See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Other information

Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep/Store only in original container. Please note safety instructions and directions for use on the drum. Handle and open container with care. Provide adequate ventilation. Do not breathe vapour/aerosol.

Protective measures

Measures to prevent fire

Usual measures for fire prevention. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Do not store in temperatures below 5 °C.

Hints on joint storage

Store the foodstuffs separately.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ACETIC ACID; CAS No.: 64-19-7

Limit value type (country of origin): TWA (EC)

Limit value: 10 ppm / 25 mg/m³

Version: 29.05.1991 Limit value type (country of origin): TLV/TWA (EC)

Page: 3 / 9

(EN / GB)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

DNEL/DMEL and PNEC values

There are no data available on the preparation itself.

DNEL/DMEL

Limit value type: DNEL Consumer (local) (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Inhalation

Exposure frequency: Long-term (repeated)

Limit value: 25 mg/m³

Limit value type : DNEL Consumer (local) (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Inhalation
Exposure frequency: Short-term (acute)
Limit value: 25 mg/m³

Limit value type: DNEL worker (local) (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Inhalation

Exposure frequency: Long-term (repeated)

Limit value: 25 mg/m³

Limit value type : DNEL worker (local) (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 25 mg/m³

PNEC

Limit value type: PNEC aquatic, freshwater (ACETIC ACID ; CAS No. : 64-19-7)

Limit value: 3,058 mg/l

Limit value type : PNEC (Industrial) (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route : Soil

Limit value : 0,478 mg/kg

Limit value type : PNEC sediment, freshwater (ACETIC ACID ; CAS No. : 64-19-7)

Limit value: 11,36 mg/kg

Limit value type: PNEC sediment, marine water (ACETIC ACID ; CAS No. : 64-19-7)

Limit value : 1,136 mg/kg

Limit value type : PNEC sewage treatment plant (STP) (ACETIC ACID ; CAS No. : 64-19-7)

Limit value : 85 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Eye glasses with side protection DIN EN 166

Skin protection

Hand protection

Short-term exposure (Level 2: < 30 min): disposable gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.1 mm.

Long-term exposure (Level 6: < 480 min): protective gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.7 mm.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Body protection

Body protection: not required.

Respiratory protection

Usually no personal respirative protection necessary.

General health and safety measures

Keep away from food, drink and animal feedingstuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing. Wash hands before breaks and after work. Separate storage of work clothes. When using do not eat, drink, smoke, sniff.

Page: 4/9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

Occupational exposure controls

Technical measures to prevent exposure

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: liquid
Colour: colourless
Odour: Acetic acid
Safety relevant basis data

Melting point/melting range: No data available Initial boiling point and boiling (1013 hPa) 100 °C approx. range: **Decomposition temperature:** No data available (1013 hPa) Flash point: not applicable Ignition temperature: not applicable Lower explosion limit: not applicable Upper explosion limit : not applicable Vapour pressure : (50°C) No data available

 Density:
 $(20 \, ^{\circ}\text{C})$ $1,15 \, ^{-}1,19$ g/cm^3

 Solvent separation test:
 $(20 \, ^{\circ}\text{C})$ < 3 %

 Water solubility:
 $(20 \, ^{\circ}\text{C})$ 100 Wt %

 pH value:
 $4,4 \, ^{-}5,4$

log P O/W: No data available

Flow time : (20 °C) < 12 s DIN-cup 4 mm

Odour threshold: No data available

Maximum VOC content (EC): 2,6 Wt %

Oxidising liquids:

Explosive properties:

Not applicable.

Not applicable.

Corrosive to metals:

Not corrosive to metals.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

None, if handled according to order.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7). Exothermal reaction with alkalis.

10.3 Possibility of hazardous reactions

Exothermal reaction with alkalis.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

None known.

SECTION 11: Toxicological information

Page: 5 / 9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

11.1 Information on toxicological effects

There are no data available on the mixture itself.

Acute effects

Acute oral toxicity

Parameter: ATEmix calculated

Exposure route : Oral
Effective dose : not relevant

Parameter: LD50 (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Oral
Species: Rat
Effective dose: 3310 mg/kg
Practical experience/human evidence

Avoid contact with skin and eyes.

Acute dermal toxicity

Parameter: ATEmix calculated

Exposure route : Dermal
Effective dose : not relevant

Parameter: LD50 (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Dermal Species: Rabbit Effective dose: 1060 mg/kg

Acute inhalation toxicity

Parameter: ATEmix calculated
Exposure route: Inhalative (vapour)
Effective dose: not relevant

Parameter: LC50 (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Inhalation
Species: Mouse
Effective dose: 5620 mg/l

Parameter: LD50 (ACETIC ACID ; CAS No. : 64-19-7)

Exposure route: Inhalation
Species: Rat
Effective dose: 4000 mg/l

Irritant and corrosive effects

No data available.

Sensitisation

No data available.

11.5 Additional information

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP].

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

There are no data available on the preparation itself.

Acute (short-term) fish toxicity

Parameter: LC50 (ACETIC ACID ; CAS No. : 64-19-7)

Species: Leuciscus idus (golden orfe)
Evaluation parameter: Acute (short-term) fish toxicity

Effective dose: 400 - 500 mg/l

Exposure time: 48 h

Parameter: LC50 (ACETIC ACID ; CAS No. : 64-19-7)

Species : Lepomis macrochirus (Bluegill)

Page: 6 / 9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date: 02.01.2018

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose: 75 mg/l Exposure time: 96 h

Parameter: LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Species: Pimephales promelas (fathead minnow)
Evaluation parameter: Acute (short-term) fish toxicity

Effective dose : 79 mg/l

Exposure time : 96 h
Acute (short-term) daphnia toxicity

Parameter: EC50 (ACETIC ACID ; CAS No. : 64-19-7)

Species: Daphnia magna (Big water flea)
Evaluation parameter: Acute (short-term) daphnia toxicity

Effective dose : 95 mg/l Exposure time : 24 h Acute (short-term) algae toxicity

Parameter: EC0 (ACETIC ACID ; CAS No. : 64-19-7)

Evaluation parameter : Acute (short-term) algae toxicity

Effective dose : 65 mg/l Exposure time : 85 h

Bacteria toxicity

Parameter: EC0 (ACETIC ACID ; CAS No. : 64-19-7)

Species: Pseudomonas putida
Evaluation parameter: Bacteria toxicity
Effective dose: 2850 mg/l
Exposure time: 16 h

12.2 Persistence and degradability

Biodegradation

No data available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

There are no data available on the preparation itself.

Adsorption/Desorption

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Concentrate/larger quantities: 09 01 04* fixer solutions.

Waste treatment options

Appropriate disposal / Product

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package

Page: 7 / 9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

National regulations

Restrictions of occupation

None

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 03. Hazardous ingredients

16.2 Abbreviations and acronyms

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimates

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CMR = Carcinogen, Mutagen or Reproductive toxicant

 CO_2 = Carbon dioxide

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = European Commission

EC50 = Half maximal effective concentration

EN = European Standard (Norm)

EU = European Union

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

 ${\sf GHS} = {\sf Globally} \ {\sf Harmonized} \ {\sf System} \ {\sf of} \ {\sf Classification} \ {\sf and} \ {\sf Labelling} \ {\sf of} \ {\sf Chemicals}$

H statement = GHS Hazard statement

IATA = International Air Transport Association ICAO-TI = International Civil Aviation Organization-Technical Instructions

Page: 8 / 9

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Periomat Intra Fixer concentrate

Revision: 02.01.2018 **Version (Revision):** 3.0.1 (3.0.0)

Print date : 02.01.2018

IMDG = International Maritime Dangerous Goods

LC50 = Median lethal concentration

LD50 = Median lethal dose

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol

of 1978. ("Marpol" = marine pollution)

NOEC/NOEL = No observed effect concentration/level

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No.

1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RMM = Risk Management Measure

RRN = REACH Registration Number

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

SVHC = Substances of Very High Concern

TLV/STEL = Threshold limit value/short-term exposure limit

TLV/TWA = Threshold limit value/time weighted average

UN = United Nations

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

16.6 Training advice

None

16.7 Additional information

Notice the directions for use on the label.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.