Page 1 of 9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020 Product code: 1550_NZL_IV		
SECTION 1: Identification of the su	bstance/mixture and of the company/unde	rtaking
1.1. Product identifier		
P icosilk 1550 0000 und 1550 0 ⁴	100	
Further trade names 1550 0000 Picosilk 75 ml 1550 0100 Picosilk 500 ml		
1.2. Relevant identified uses of the sul	bstance or mixture and uses advised against	
Use of the substance/mixture		
Release agent to release the su	face of casting waxes.	
Uses advised against No information available.		
1.3. Details of the supplier of the safet	y data sheet	
Manufacturer Company name: Street: Place: Telephone:	Renfert GmbH Untere Giesswiesen 2 D-78247 Hilzingen +49 7731 8208-0	Telefax: +49 7731 8208-70
e-mail: Internet:	info@renfert.com www.renfert.com	
Supplier Company name: Street: Place: Telephone:	Ivoclar Vivadent Ltd New Zealand 12 Omega St GB Rosedale, Auckland +64 9 914 9999	Telefax: +64 9 914 9990
Internet:	www.ivoclarvivadent.co.nz	Telelax. +04 9 914 9990
<u>1.4. Emergency telephone</u> number:	0800 764 766 (National Poison Centre) Poisons Hotline (24 hours / 7 days)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol Signal word: Da

Danger

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550_NZL_IV

Page 2 of 9





Hazard statements

H225	Highly flammable liquid and vapour.			
H319	Causes serious eye irritation.			
H336	May cause drowsiness or dizziness.			
acquitionary statements				

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye/face protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Wetting agent (tensides)

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No		REACH No	
	GHS Classification			
67-63-0	propan-2-ol			> 60 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts		< 10 %	
	307-055-2		01-2119489924-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H302 H315 H318 H412		318 H412	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Immediately remove any contaminated clothing, shoes or stockings.

After inhalation

Provide fresh air.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550_NZL_IV

Page 3 of 9

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Use personal protection equipment. Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Avoid contact with eyes and skin. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges .

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550_NZL_IV

Page 4 of 9

Hints on joint storage

Do not store together with: Oxidizing agent

Further information on storage conditions

Protect against: Heat

Do not store at temperatures below 10°C

7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work . Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 8 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic

pH-Value (at 20 °C):

Test method

7

5 of 9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100 Revision date: 23.11.2020 Product code: 1550_NZL_IV Page 5				
not determined				
82 °C				
15 °C DIN 51755				
not applicable				
not applicable				
2,0 * vol. %				
12,0 * vol. %				
425 * °C				
not applicable not applicable				
not determined				
48 * hPa				
0,825 - 0,835 g/cm³				
miscible				
not determined				
	1550 0000 und 1550 0100 duct code: 1550_NZL_IV not determined 82 °C 15 °C DIN 51755 not applicable not applicable not applicable not applicable not applicable not determined 48 * hPa 0,825 - 0,835 g/cm ³ miscible not determined not determined not determined not determined not determined			

* Data apply to the main component.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Strong acid Incompatible materials: Oxidizing agent In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550_NZL_IV

Page 6 of 9

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts				
	oral	LD50 500 - 2000 mg/kg	Rat	OECD 401	
	dermal	LD50 > 2000 mg/kg	Mouse		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method
67-63-0	propan-2-ol				
	Acute bacteria toxicity	(> 100 mg/l)			
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts				
	Acute fish toxicity	LC50 1 - 10 mg/l	96 hBrachydanio rerio (zebra-fish)		OECD 203
	Acute algae toxicity	ErC50 > 61 mg/l	72 h Desmodesmus subspicatus		OECD 201
	Acute crustacea toxicity	EC50 9,81 mg/l	48 h Daphnia magna (Big water flea)		OECD 202

12.2. Persistence and degradability

The surfactant contained in this mixture complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550_NZL_IV

Page 7 of 9

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts					
OECD 301B 78 % 28						
	Readily biodegradable (according to OEC	CD criteria).				
	OECD 301E	89 %	28			
	Readily biodegradable (according to OECD criteria).					
	OECD 303A 96,2 % 34					
	Biodegradable.					

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
	3
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL
14.3. Transport hazard class(es):	3

according to Regulation (EC) No 1907/2006

Pavisian data: 22.11.2020	Picosilk 1550 0000 und 1550 0100 Product code: 1550 NZL IV	Dage 9 of 0	
Revision date: 23.11.2020		Page 8 of 9	
<u>14.4.</u> Packing group:	II		
Hazard label:	3		
Marine pollutant:	no		
Air transport (ICAO-TI/IATA-DGR)			
<u>14.1. UN number:</u>	UN 1219		
<u>14.2. UN proper shipping name:</u>	ISOPROPANOL		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
	₩		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	no		
<u>14.6.</u> <u>Special precautions for user</u> Further information: see section 6,	7 8		
14.7. Transport in bulk according to An			
not applicable			
SECTION 15: Regulatory information			
15.1. Safety, health and environmental re	gulations/legislation specific for the substance or mixture		
	<u> </u>		
Classified as Hazardous according	to the criteria of the National Occupational Health and Safety Commission	n (NOHSC)	
approved criteria for the classifying hazardous substances [NOHSC: 1008] 3rd edition.			
Standard for the Uniform Schedulir Carcinogen classification under WI			
	ith section 3 and current national legislation.		
HSNO Approval: HSR001180			
EPA NZ Classes of hazardous pro			
Classification 3.1B Flammable liqu			
Classification 6.1E (All) Substance Classification 6.1E (O)	s that are acutely toxic – May be harmful, aspiration hazard		
Classification 6.1E (I)			
Classification 6.3B Substances that	t are mildly irritating to the skin		
Classification 6.4A Substances that			
SECTION 16: Other information			
Abbreviations and acronyms			
PBT: Persistent Bioaccumulative and Toxic			

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative CAS: Chemical Abstracts Service (division of the American Chemical Society) LD50: lethal dose, 50% LC50: lethal concentration, 50%

according to Regulation (EC) No 1907/2006

Picosilk 1550 0000 und 1550 0100

Revision date: 23.11.2020

Product code: 1550 NZL IV

Page 9 of 9

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
-	
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eyeirritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)