

No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product MK-dent PREMIUM SERVICE OIL (LU1022)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sector of uses [SU]

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Recommended intended purpose(s)

Lubricant

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor MK-dent GmbH

Marie-Curie-Straße 2, D-22941 Bargteheide

Phone +49(0)4532-400490, Fax +49(0)4532-4004910

E-Mail info@mk-dent.com Internet www.mk-dent.com

Advice Produktinformation / Product Information Phone

+49(0)4532-400490 Fax +49(0)4532-4004910

Importer/Distributor Company name: Ivoclar Vivadent Pty Ltd

Place: 1-5 Overseas Drive Noble Park North VIC 3174 Telephone: +61 3 9795 9599 Telefax:Fax: +61 3 9795 9645

e-mail: info@ivoclarvivadent.com

1.4. Emergency telephone number 131 126 (Poisons Information Centre - 24 hours / 7 days)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Aerosol 1 H222, H229

Compr. Gas

Aquatic Chronic 3 H412

! Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

! Hazard statements for environmental hazards

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS04



No. 1907/2006 (REACH)
Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

! Signal word

Danger

! Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

! Hazard statements for environmental hazards

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

General

P102 Keep out of reach of children.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

! Storage

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

! Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

! Special rules for supplemental label elements for certain mixtures

Contains peppermint oil. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

ester oil

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
74-98-6	200-827-9	propane	26,1	Flam. Gas 1, H220 / Press. Gas
75-28-5	200-857-2	isobutane	26,1	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	26,1	Flam. Gas 1, H220 / Press. Gas
540-84-1	208-759-1	2,2,4-trimethylpentane	1,7	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
8006-90-4	308-770-2	peppermint oil	0,2	Asp.Tox. 1, H304 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take affected person into fresh air.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of irritation consult a doctor.

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Remove contact lens.

In case of ingestion

Do not induce vomiting.

Medical treatment.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Breathing protection and eye protection is required for fire-fighting under presence of fume and vapour

Additional information

Cool endangered containers with water spray and possibly remove them from fire site.

Collect contaminated firefighting water separately, must not be discharged into the drains.



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid skin and eye contact

For emergency responders

Remove persons to safety.

Keep people away and stay on the upwind side.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Take up with absorbent material.

Additional Information

Inform competent authorities in case of leakage to sewage system/surface water/groundwater.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

General protective measures

Take the usual precautions when handling with chemicals.

Hygiene measures

Please observe work hygiene regulations.

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Keep away from foods and beverages.

Keep away from ignition sources.

Store at distance to oxidising agents.

Do not store together with alkalies.

Keep at distance to acids.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from direct solar radiation.

Protect from heat and direct solar radiation.



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

7.3. Specific end use(s) Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrilrubber (index 1) The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN374.

The exact breakthrough time of the glove material is to be inquired from the protection glove manufacturer and must be strictly adhered to.

Eye protection

safety goggles with side protection

Other protection measures

Protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdouraerosolyellowishcharacteristic

Odour threshold No data available

Important health, safety and environmental information

 Value
 Temperature
 at
 Method
 Remark

 pH value
 not determined

 Boiling temperature / boiling range
 not determined

Melting point / Freezing

point

not determined

Flash point ca. -80 °C

Vapourisation rate not determined



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

	Value	Temperature	at	Method	Remark
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	ca. 400 °C				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	not determined				
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Oxidising properties No information available.					
Explosive properties Does not apply; nevertheless	can be produced e	explosive vapour/a	air mixtures		

! SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known.

10.2. Chemical stability

9.2. Other information

Stable under the stated storage temperature.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reactions with oxidising agents.

10.4. Conditions to avoid

strong heating sunlight



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

10.5. Incompatible materials

! Substances to avoid

strong acids oxidizing agent alkalis

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

Additional information

No risk of production of decomposition products when appropriately handled and stored

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	No data available			
LD50 acute dermal	No data available			
LC50 acute inhalation	No data available			
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	No data available			
Sensitization respiratory system	No data available			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Subacute Toxicity	No data available			
Subchronic Toxicity	No data available			
Chronic Toxicity	No data available			
Mutagenicity	No data available			
Reproduction- Toxicity	No data available			
Carcinogenicity	No data available			



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

Specific target organ toxicity (single exposure)

no

Specific target organ toxicity (repeated exposure)

no

Aspiration hazard

no

Toxicity test (Additional information)

No data available

Experiences made from practice

No data available

Additional information

No toxical dates available.

Other hazardous properties may not be excluded.

The product is to be handled with the caution usual with chemicals.

! SECTION 12: Ecological information

12.1. Toxicity

LCOto	VICA	Ivaival	Attacte
LCUIL	ハー	iouicai	effects

Ecotoxicolo	Value	•	Species	Method	Validation
Fish	LC50 0,1	11 mg/l (96 h)	Oncorhynchus	mykiss	2,2,4-Trimethylpentan
Daphnia	a EC50 0,4 mg/l (48 h)		Daphnia magna	a	2,2,4-Trimethylpentan
Algae	lgae NOEL 0,658 ml/g (72 h)		Pseudokirchnerella subcapitata		2,2,4-Trimethylpentan
Bacteria	No data	available.			
12.2. Persist		egradability Elimination rate	Method of analysis	Method	Validation
Physico-che degradability	iiiioai	No data available.			
Biological	2	22,4 % (28 d)			Moderately/partially biodegradable

degradability 2,2,4-Trimethylpentan

Degradability No data available.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

If handled in the appropriate manner, no adverse effects on the environment are known and to be expected.

Ecological data are not available.

Do not allow uncontrolled leakage of product into the environment.



No. 1907/2006 (REACH) Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No. Name of waste 15 01 04 metallic packaging

Recommendations for the product

Consult the appropriate local waste disposal expert about waste disposal.

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of in accordance with legal regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

The waste code must be allocated in compliance with the EAK-regulation referring to the specific process and the sector.

The classification of waste is always the responsibility of the end user.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D Classification code 5F

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classified as Hazardous according to the criteria of the National Occupational Health and Safety Commission (NOHSC) approved criteria for the classifying hazardous substances [NOHSC: 1008] 3rd edition.

Standard for the Uniform Scheduling of Medicines and Poisons.

Carcinogen classification under WHS Regulation 2011, Schedule 10.

Notification status in accordance with section 3 and current national legislation.



No. 1907/2006 (REACH)
Printed 18.12.2017

Revision 12.12.2017 (GB) Version 2.0 **MK-dent PREMIUM SERVICE OIL (LU1022)**

HSNO Approval: HSR001010, HSR000989, HSR001176, HSR003779

EPA NZ Classes of hazardous properties:

Classification 2.1 1A Flammable Gases: high hazard Classification 3.1B Flammable Liquids: high hazard

Classification 6.1E (All) Acutely toxic

Classification 6.3B Mildly irritating to the skin

Classification 6.4A Irritating to the eye

Classification 9.1A (All) Very ecotoxic in the aquatic environment

Classification 3.1D Flammable Liquids: low hazard

Classification 6.1E (All) Acutely toxic Classification 6.3A Irritating to the skin

Classification 6.4A irritating to the eye

Classification 9.1D (All) Slightly harmful in the aquatic environment or are otherwise designed for biocidal action

Classification 9.2D Slightly harmful in the soil environment

Other regulations (EU)

Aerosol directive (75/324/EEC).

15.2. Chemical Safety Assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

H220

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.0

Sources of key data used

Data sheets of the sub-supplier.

Extremely flammable gas

11220	Extremely hammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.