

#### **Material Safety Data Sheet**

For ZHUHAI JINWO ELECTRONIC TECHNOLOGY Co., Ltd No.35, Yongan Three Road, Hongqi Town, Jinwan District, Zhuhai, Guangdong, China.

And for their product

Li-ion Battery

Model/type reference	: LI-ION16500-JW-NO24
Nominal Voltage	: 3.7V
Rated Capacity	: 1200mAh (4.44Wh)
Version number	: V1.0
Revision date	: N/A

Laboratory:	Shenzhen NTEK Testing Technology Co., Ltd.
Address	1/F, Building C, Fenda Science Park, Sanwei Community, Xixiang
	Street, Bao'an District, Shenzhen 518126 P. R. China

		Testing Tech
Compiled by (name+ signature):	Jonea Wu	NR INFREMA
Approved by (+ signature)	Karl Huang	Berl Wang w

Shenzhen NTEK Testing Technology Co., Ltd. Address: 1/F, Building C, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China Tel: +86-755-6115 6588 Fax: +86-755-6115 6599 Http://www.ntek.org.cn

### Section 1- Chemical Product and Company Identification

Product Identification: Li-ion Battery Model No.: LI-ION16500-JW-NO24 Manufacturer's / Supplier Name: ZHUHAI JINWO ELECTRONIC TECHNOLOGY CO., LTD. Address: No.35, Yongan Three Road, Hongqi Town, Jinwan District, Zhuhai, Guangdong, China. Telephone number of the supplier: +86-756-8639509 Emergency Telephone No. (24h): +86-756-8639509 Fax: N/A E-mail address: yxh052529009@sina.com Preparation Date: 2020-02-26 Effective date: 2020-01-01 ~ 2020-12-31 This MSDS was prepared by Shenzhen NTEK Testing Technology Co., Ltd. Item Number: S20010902910001 Referenced documents: ISO 11014:2009 Safety data sheet for chemical products

#### Importer/ Distributer

Company name: Ivoclar Vivadent Ltd Place: PO Box 303011, North Harbour, Auckland, 0751 Telephone: +64 9 914 9999 Telefax: +64 9 914 9990

**Emergency telephone number**: 0800 764 766 Poison Hotline (24 hours / 7 days) NZ: National Poison Centre (New Zealand)

#### Section 2 – Hazards Identification

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shred the Li-ion Battery ingredients contained within or their ingredients products could be harmful.
Apperance, Color, and Odor	Solid object with no odor, no color.
Primary Route(s) of Exposure	These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact

Potential	ACUTE (short term): see Section 8 for exposure controls In the event that this
Health Effects:	battery has been ruptured, the electrolyte solution contained within the battery
Lileota.	would be corrosive and can cause burns.
	Inhalation: Inhalation of materials from a sealed battery is not an expected route of
	exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.
	Ingestion: Swallowing of materials from a sealed battery is not an expected route
	of exposure. Swallowing the contents of an open battery can cause serious
	chemical burns of mouth, esophagus, and gastrointestinal tract.
	Skin: Contact between the battery and skin will not cause any harm. Skin contact
	with contents of an open battery can cause severe irritation or burns to the skin.
	Eye: Contact between the battery and the eye will not cause any harm. Eye contact
	with contents of an open battery can cause severe irritation or burns to the eye.
	CHRONIC (long term): see Section 11 for additional toxicological data



Medical	Not applicable
Conditions	
Aggravated by Exposure	
Reported as carcinogen	Not applicable

### Section 3 – Composition/Information on Ingredients

Li-ion Battery is a mixture.

Hazardous Ingredients	Concentration or	CAS Number
(Chemical Name)	concentration ranges (%)	
Lithium cobalt oxide (LiCoO <sub>2</sub> )	36	12190-79-3
Carbon	15	1333-86-4
Copper foil	10	7440-50-8
Aluminum foil	20	7429-90-5
Other	19	N/A

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not applicable.

### Section 4 – First-aid Measures

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or	
	move victim to fresh air. Obtain medical advice.	
Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible	
	remove contaminated clothing, shoes and leather goods. Immediately flush with	
	lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists,	
	seek medical attention. Completely decontaminate clothing, shoes and leather	
	goods before reuse or discard.	
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the	
	contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes	
	while holding the eyelids open. Neutral saline solution may be used as soon as it is	
	available. If necessary, continue flushing during transport to emergency care	
	facility. Take care not to rinse contaminated water into the unaffected eye or onto	
	face. Quickly transport victim to an emergency care facility.	

Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if
	victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim
	rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim
	drink 60 to 240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean
	forward to reduce risk of aspiration. Have victim rinse mouth with water again.
	Quickly transport victim to an emergency care facility.

# Section 5 – Fire-fighting Measures

Flammable	In the event that this battery has been ruptured, the electrolyte solution contain
Properties	within the battery would be flammable. Like any sealed container, battery cells may
	rupture when exposed to excessive heat; this could result in the release of
	flammable or corrosive materials.

Suitable	
extinguishing	Use extinguishing media suitable for the materials that are burning.
Media	
Unsuitable	
extinguishing	Not available
Media	
Explosion	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases
Data	Sensitivity to Static Discharge: Not Applicable
Specific	Fires involving Li-ion Battery are controlled with water. When water is used,
Hazards	however, hydrogen gas may evolve. In a confined space, hydrogen gas can form
arising from	an explosive mixture. In this situation, smothering agents are recommended to
the chemical	extinguish the fire
Protective	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a
Equipment	
and	pressure-demand, self-contained breathing apparatus and full protective gear.
precautions	Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved
for firefighters	full-face self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0

# Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and	Restrict access to area until completion of
emergency procedures	clean-up. Do not touch the spilled material. Wear
	adequate personal protective equipment as
	indicated in Section 8.

Environmental Precautions	Prevent material from contaminating soil and
	from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled
	liquid with dry sand or earth. Clean up spills
	immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent
	(dry sand or earth). Scoop contaminated
	absorbent into an acceptable waste container.
	Collect all contaminated absorbent and dispose
	of according to directions in Section 13. Scrub
	the area with detergent and water; collect all
	contaminated wash water for proper disposal.

# Section 7 – Handling and Storage

Handling	Don't handle Li-ion Battery with metalwork. Do not open, dissemble, crush or burn battery. Ensure good ventilation/ exhaustion at the workplace. Prevent formation of dust. Information about protection against explosions and fires: Keep ignition sources away- Do not smoke.
Storage	If the Li-ion Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Li-ion Battery periodically. 3 months: -10°C~+40°C, 45 to 85%RH And recommended at 0°C~+35°C for long period storage.
	The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.
	The voltage for a long time storage shall be 3.7V~4.2V range.
	Do not store Li-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
	Keep out of reach of children.
	Do not expose Li-ion Battery to heat or fire. Avoid storage in direct sunlight.
	Do not store together with oxidizing and acidic materials.

### Section 8 – Exposure Controls and Personal Protection

Engineering Controls	Use local exhaust ventilation or other
5 5	engineering controls to control sources of dust,
	mist, fumes and vapor.
	Keep away from heat and open flame. Store in a
	cool, dry place.
Personal Protective Equipment	Respiratory Protection: Not necessary under
	normal conditions.
	Skin and body Protection: Not necessary
	under normal conditions, Wear neoprene or
	nitrile rubber gloves if handling an open or
	leaking battery.
	Hand protection: Wear neoprene or natural
	rubber material gloves if handling an open or
	leaking battery.
	Eye Protection: Not necessary under normal
	conditions, Wear safety glasses if handling an
	open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain
	readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area.
	Maintain good housekeeping.

### Section 9 - Physical and Chemical Properties

	Physical Color: Blue	
Physical State		
olulo	Odor: Odorless	
Change in c	condition:	
pH, with ind	ication of the concentration	Not applicable
Melting poir	nt/freezing point	Not available.
Boiling Poin range:	t, initial boiling point and Boiling	Not available.
Flash Point		Not available.
Upper/lowe	r flammability or explosive limits	Not available.
Vapor Pres	sure:	Not applicable

Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.
Solubility in Water:	Insoluble
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	130°C
Decomposition temperature	Not available.
Odout threshold	Not available.
Evaporation rate	Not available.
Flammability (soil, gas)	Not available.
Viscosity	Not applicable

## Section 10 - Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Li-ion Battery to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not Available

## Section 11 - Toxicological Information

Irritation	Risk of irritation occurs only if the cell is
	mechanically, thermally or electrically abused to
	the point of compromising the enclosure. If this
	occurs, irritation to the skin, eyes and respiratory
	tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available

Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

#### Section 12 - Ecological Information

General note:	Water hazard class 1(Self-assessment): slightly
	hazardous for water.
	Do not allow undiluted product or large quantities
	of it to reach ground water, water course or
	sewage system.
Anticipated behavior of a chemical product in	Not Available
environment/possible environmental	
impace/ecotoxicity	
Mobility in soil	Not Available

Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available

#### Section 13 – Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations. Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

#### Section 14 – Transport Information

The Li-ion Battery (LI-ION16500-JW-NO24) had passed the UN 38.3 test and is classified as non-dangerous goods and also complies with the UN Recommendations on the Transport of Dangerous Goods; IATA Dangerous Goods regulations, and applicable U.S. DOT regulations for the safe transport of Li-ion Battery.

The Li-ion Battery is transported according to the PACKING INSTRUCTION 967 Section  $\,\mathrm{II}\,\text{of}$ 

IATA DGR 61<sup>st</sup> edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, UN No.: UN3481).

However, the Li-ion Battery may also be transported according to the PACKING INSTRUCTION 965 Section I B of IATA DGR 61<sup>st</sup> edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES, UN No.: UN3480) or PACKING INSTRUCTION 966 Section II of IATA DGR 61<sup>st</sup> edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES PACKED WITH EQUIPMENT, UN No.: UN3481).

More information concerning shipping, testing, marking and packaging can be obtained from label master at http://www.labelmaster.com/.

Each package must be labeled with a Lithium Battery handling label.

Li-ion batteries can be treated as "Non-dangerous goods" under the United Nations

Recommendations on the Transport of Dangerous Goods, Special Provision 188, provided that packaging is strong and prevent the products from short-circuit.

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions (2019-2020 edition).
- The International Air transport Association (IATA) Dangerous Goods Regulations (61<sup>st</sup> edition).
- The International Maritime Dangerous Goods (IMDG) Code (Amdt. 39-18).
- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA

- The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA)

#### Section 15 - Regulatory Information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Classified as Hazardous according to the criteria of the National Occupational Health and Safety Commission (NOHSC) approved criteria for the classifying hazardous substances [NOHSC: 1008] 3rd edition.

Standard for the Uniform Scheduling of Medicines and Poisons.

Carcinogen classification under WHS Regulation 2011, Schedule 10.

Notification status in accordance with section 3 and current national legislation.

HSNO Approval: HSR006615, HSR002948, HSR001474

EPA NZ Classes of hazardous properties:

Classification 6.3B Mildly irritating to the skin

Classification 6.7B Suspected human carcinogens

Classification 6.1B (All) Substances that are acutely toxic - Fatal

Classification 6.1B (O)

Classification 6.1B (I)

Classification 6.4A Substances that are irritating to the eye

Classification 6.5B Substances that are contact sensitisers

Classification 6.6A Substances that are known or presumed human mutagens

Classification 6.9B (All) Substances that are harmful to human target organs or systems

Classification 6.9B (O)

Classification 6.9B (I)

Classification 9.1A (All) Substances that are very ecotoxic in the aquatic environment

Classification 9.1A (F)

Classification 9.1A (C)

Classification 9.1A (A)

Classification 9.1A (Oth)

Classification 9.2D Substances that are slightly harmful in the soil environment

Classification 9.3A Substances that are very ecotoxic to terrestrial vertebrate

Classification 4.2A Spontaneously Combustible Substances: pyrophoric substances: high hazard

#### **Section 16 - Other Information**

The information above is believed to be accurate and represents the best information currently available to us. However, NTEK makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.